

TERRA TRAX - Tekniska specifikationer

Description

TERRA TRAX har specialutformats för utfodringsredskap. Det lämpar sig för både väg- och terrängkörning. TERRA TRAX har utmärkta prestanda på vägen, hög körkomfort och självrensningfunktioner. Det låga rullningsmotståndet bidrar till bättre bränsleekonomi.

UM

US Standard

Construction

✚ BIAS

Machinery

Lantbruk: Arbetsfordon



Version	STANDARD
Type	TL
Tyre Size	400/45L - 17.5

Dimensions US Standard

Usa code	94063451
Ply Rating	14
Section Width (inch)	15.6
Overall Diameter (inch)	30.9
Static Loaded Radius (inch)	14.2
Rolling Circumference (inch)	93.3
Rim Rec	14.00
ECE	E11-106R-006002

Load capacity (lbs)

mph / psi	87
25	8800

Printed on 4/27/2024 8:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..