

TF 8181 - Tekniska specifikationer



Description

TF 8181 är ett fält- och vägorienterat däck konstruerat för tvåhjulsdrevna traktorer som används till jordbearbetnings- och transportarbeten. Däcket erbjuder utmärkt styrningsprestanda.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Tvåhjulsdreven traktor
Industri: Släpvagn

Version	STANDARD
Type	TT
Tyre Size	6.00 - 16
LI/SS	85 A8

Dimensions US Standard

Usa code	94020584
Ply Rating	6
Section Width (inch)	6.8
Overall Diameter (inch)	29.3
Static Loaded Radius (inch)	13.8
Rolling Circumference (inch)	87.4
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5 K ; 5.00 F
ECE	E4-106R-001959
TRA Code	F2

Load capacity (lbs)

mph / psi	52
25	1140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 5:39 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..