

TF 8181 - Tekniska specifikationer



Description

TF 8181 är ett fält- och vägorienterat däck konstruerat för tvåhjulsdreven traktorer som används till jordbearbetnings- och transportarbeten. Däcket erbjuder utmärkt styrningsprestanda.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Tvåhjulsdreven traktor
Industri: Släpvagn

Version	IMPLEMENT
Type	TT
Tyre Size	7.50 - 16
LI/SS	122 A6

Dimensions International Standard

Ply Rating	14
Section Width (mm)	205
Overall Diameter (mm)	820
Static Loaded Radius (mm)	383
Rolling Circumference (mm)	2445
Rim Rec	5.50 F
Rim Alt	5.00 F ; 5 K ; 6.00 F
ECE	E4-106R-002670
TRA Code	F2

Load capacity (Kg)

km/h / bar	5.50
30	1500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/05/2025 13:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..