

TF 9090 - Tekniska specifikationer



Description

TF 9090 är ett däck konstruerat för små traktorer som används till jordbearbetning. Specialmönstret ger utmärkt styrningsprestanda på lös jord.

UM

International Standard

Construction



Machinery

Lantbruk: Liten traktor Industri: Släpvagn

| Version | SPECIAL |
|-----------|-----------|
| Туре | ΤΤ |
| Tyre Size | 7.50 - 18 |
| II/SS | 101 A6 |

Dimensions International Standard

| Ply Rating | 6 |
|----------------------------|--------|
| Section Width (mm) | 207 |
| Overall Diameter (mm) | 860 |
| Static Loaded Radius (mm) | 404 |
| Rolling Circumference (mm) | 2562 |
| Rim Rec | 5.50 F |
| TRA Code | F2 |

Load capacity (Kg)

| km/h / bar | 2.80 |
|------------|------|
| 30 | 825 |

Printed on 4/23/2024 10:30 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..