



TF 9393 - Tekniska specifikationer



Description

TF 9393 är ett framhjul för lantbruket som har tagits fram speciellt för små traktorer som används till jordbearbetning och lämpar sig särskilt för lös jord. Mönstret är bredare i mitten och ribbat på skuldran. Specialmönstret ger utmärkt styrningsprestanda på alla underlag.

UM

US Standard

Construction

❖ BIAS

Machinery

Lantbruk: Liten traktor

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	103 A6

Dimensions US Standard

Usa code	94046263
Ply Rating	8
Section Width (inch)	8.3
Overall Diameter (inch)	31.9
Rim Rec	5.50 F
Rim Alt	5.00 F ; 6.00 F
TRA Code	F2

Load capacity (lbs)

mph / psi	56
25	1545

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 3:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..