

TR 117 - Tekniska specifikationer



Description

TR 117 är idealiskt för irrigationsarbeten med bevattningsramp. Det specialutformade mönstret ger utmärkt dragförmåga och enastående självrensande egenskaper.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Roterande bevattningsmaskin

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 11.2 - 38 |
| LI/SS | 109 A6 |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Ply Rating | 4 |
| Section Width (mm) | 284 |
| Overall Diameter (mm) | 1445 |
| Static Loaded Radius (mm) | 675 |
| Rolling Circumference (mm) | 4400 |
| Rim Rec | W 10 |
| Rim Alt | W 9 |
| ECE | E4-106R-002747 |
| TRA Code | R1 |

Load capacity (Kg)

| km/h / bar | 1.30 | 1.70 |
|------------|------|------|
| 30 | 1030 | --- |
| CREEP | --- | 2005 |

* - CREEP SPEED - 200 FT/30 MIN (61 M/30 MIN)

Printed on 4/19/2024 8:26 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..