

## TR 117 - Tekniska specifikationer



### Description

TR 117 är idealiskt för irrigationsarbeten med bevattningsramp. Det specialutformade mönstret ger utmärkt dragförmåga och enastående självrensande egenskaper.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Roterande bevattningsmaskin

Version	STANDARD
Type	TT
Tyre Size	13.6 - 24
LI/SS	115 A8

## Dimensions US Standard

Usa code	94046805
Ply Rating	6
Section Width (inch)	13.8
Overall Diameter (inch)	46.7
Static Loaded Radius (inch)	21.3
Rolling Circumference (inch)	141.4
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-004419
TRA Code	R1

## Load capacity (lbs)

mph / psi	22	41
25	2680	---
CREEP	---	5655

\* - CREEP SPEED - 200 FT/30 MIN ( 61 M/30 MIN )

Printed on 4/19/2024 11:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..