

## TR 126 - Tekniska specifikationer



### Description

TR 126 är konstruerat för att passa små traktorer som används till jordbearbetning. De djupa däccklackarna och mönstret erbjuder utmärkt dragförmåga och enastående lastkapacitet, vilket ger den bästa däckprestandan i alla arbetsförhållanden.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Liten traktor

Version	STANDARD
Type	TT
Tyre Size	7 - 14
LI/SS	92 A8

## Dimensions US Standard

Usa code	94052639
Ply Rating	8
Section Width (inch)	6.7
Overall Diameter (inch)	27.2
Static Loaded Radius (inch)	12.6
Rolling Circumference (inch)	81.5
Rim Rec	5 JA ; 5 KB
ECE	E11-106R-005233
TRA Code	R1

## Load capacity (lbs)

mph / psi	58
25	1390

Printed on 4/23/2024 8:10 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..