



## TR 128 - Tekniska specifikationer



### Description

TR 128 är särskilt konstruerat för bruksfaktorer och jordfräsar. Den breda och djupa däckklacksdesignen och gummiblandningens speciella motståndskraft mot skärande underlag och punkteringar ger extra lång livslängd. TR 128 ger maximal dragförmåga på våt mark.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Lantbruk: Jordfräs • Universalfordon

Version	STANDARD
Type	TT
Tyre Size	180/85 D 12
LI/SS	63 A6

## Dimensions US Standard

Usa code	94058129
Ply Rating	4
Section Width (inch)	6.5
Overall Diameter (inch)	24.1
Static Loaded Radius (inch)	11.6
Rolling Circumference (inch)	72.7
Rim Rec	5 JA
ECE	E11-106R-004821

## Load capacity (lbs)

mph / psi	23
20	600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 10:54 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..