

TR 128 - Tekniska specifikationer



Description

TR 128 är särskilt konstruerat för bruksfaktorer och jordfräsar. Den breda och djupa däckklacksdesignen och gummiblandningens speciella motståndskraft mot skärande underlag och punkteringar ger extra lång livslängd. TR 128 ger maximal dragförmåga på våt mark.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Jordfräs • Universalfordon

Version	STANDARD
Type	TT
Tyre Size	6.00 - 12
LI/SS	72 A8

Dimensions US Standard

Usa code	94045242
Ply Rating	6
Section Width (inch)	6.3
Overall Diameter (inch)	25
Static Loaded Radius (inch)	11.7
Rolling Circumference (inch)	75.8
Rim Rec	4.00 E
Rim Alt	4.00 E DT
ECE	E11-106R-003479

Load capacity (lbs)

mph / psi	38
25	785

Printed on 4/18/2024 8:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..