

TR 128 - Ladda ned faktablad



Description

TR 128 är särskilt konstruerat för bruksfaktorer och jordfräsar. Den breda och djupa däccklacksdesignen och gummblandningens speciella motståndskraft mot skärande underlag och punkteringar ger extra lång livslängd. TR 128 ger maximal dragförmåga på våt mark.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Jordfräs • Universalfordon

| SIZE | Version | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|-------------|----------|-------|----|---------|-----------|-----|-----|-----|------|------|-----------------|
| 180/85 D 12 | STANDARD | 63 A6 | 4 | 5 JA | | 165 | 612 | 295 | 1847 | TT | E11-106R-004821 |
| 180/85 D 12 | STANDARD | 76 A6 | 6 | 5 JA | | 165 | 612 | 295 | 1847 | TT | E11-106R-005207 |
| 5 - 12 | STANDARD | | 4 | 4 JA | | 127 | 554 | 262 | 1700 | TT | E11-106R-003477 |
| 5 - 12 | STANDARD | 64 A6 | 6 | 4 JA | | 127 | 554 | 262 | 1700 | TT | E11-106R-005189 |
| 6.00 - 12 | STANDARD | 69 A6 | 4 | 4.00 E | 4.00 E DT | 160 | 635 | 296 | 1926 | TT | E11-106R-003478 |
| 6.00 - 12 | STANDARD | 76 A6 | 6 | 4.00 E | 4.00 E DT | 160 | 635 | 296 | 1926 | TT | E11-106R-003479 |
| 6.00 - 12 | STANDARD | 82 A6 | 8 | 4.00 E | 4.00 E DT | 160 | 635 | 296 | 1926 | TT | |
| 7 - 14 | STANDARD | 95 A6 | 8 | 5 JA | 5 J | 173 | 690 | 323 | 2086 | TT | E11-106R-004093 |

Printed on 4/18/2024 6:11 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..