

TR 133 - Ladda ned faktablad



Description

TR 133 är specialdesignat för traktorer som används till jordbearbetning. Tack vare det stora antalet däckklackar ger däcket utmärkt dragförmåga och besitter även utökade rensande egenskaper. TR 133 har extra lång livslängd.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Traktor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
13.6 - 38 (14.00 - 38)	STANDARD	R1	136 A6	10	W 12	W 11	350	1580	735	4843	750	TT	E11-106R-003549

Printed on 4/16/2024 11:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..