

## TR 136 - Tekniska specifikationer



### Description

TR 136 har utvecklats av BKT för att utrusta traktorer och släpvagnar inom jordbearbetning och transportarbeten. Det här däck erbjuder bättre dragförmåga under alla arbetsförhållanden, liksom maximalt motstånd mot skärande underlag och punkteringar för att reducera maskinens driftstopp och höja produktiviteten. Tack vare ett större antal däckklackar ger TR 136 enastående dragförmåga även vid tung last.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Traktor • Släpvagn

Version	STANDARD
Type	TT
Tyre Size	12.4 - 28
LI/SS	120 A8

## Dimensions US Standard

Usa code	94036417
Ply Rating	8
Section Width (inch)	12.4
Overall Diameter (inch)	50.2
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	147.6
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-003551
TRA Code	R1

## Load capacity (lbs)

mph / psi	34
25	3090

Printed on 11/28/2023 1:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..