

TR 136 - Tekniska specifikationer



Description

TR 136 har utvecklats av BKT för att utrusta traktorer och släpvagnar inom jordbearbetning och transportarbeten. Det här däck erbjuder bättre dragförmåga under alla arbetsförhållanden, liksom maximalt motstånd mot skärande underlag och punkteringar för att reducera maskinens driftstopp och höja produktiviteten. Tack vare ett större antal däckklackar ger TR 136 enastående dragförmåga även vid tung last.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Traktor • Släpvagn

Version	SPECIAL
Type	TL
Tyre Size	16.9 - 30
LI/SS	143 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	429
Overall Diameter (mm)	1485
Static Loaded Radius (mm)	687
Rolling Circumference (mm)	4523
SRI (mm)	700
Rim Rec	W 15 L
Rim Alt	W 14 L
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.40
30	2725

Printed on 4/25/2024 7:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..