

TR 136 - Ladda ned faktablad



Description

TR 136 har utvecklats av BKT för att utrusta traktorer och släpvagnar inom jordbearbetning och transportarbeten. Det här däck erbjuder bättre dragförmåga under alla arbetsförhållanden, liksom maximalt motstånd mot skärande underlag och punkteringar för att reducera maskinens driftstopp och höja produktiviteten. Tack vare ett större antal däckklackar ger TR 136 enastående dragförmåga även vid tung last.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Traktor • Släpvagn

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
18.4 - 26	SPECIAL	R1	146 A6	12	W 16 L	W 15 L	480	1450	646	4205	675	TL	E11-106R-003614
18.4 - 26	STANDARD	R1	150 A6	14	W 16 L	W 15 L	480	1450	646	4205	675	TL	E4-106R-002301
18.4 - 26	STANDARD	R1	146 A6	12	W 16 L	W 15 L	480	1450	646	4205	675	TL	
18.4 - 26	STANDARD	R1	146 A6	12	W 16 L	W 15 L	480	1450	646	4205	675	TT	E4-106R-002718
12.4 - 28	STANDARD	R1	123 A6	8	W 11	W 9 ; W 10	315	1275	595	3749	600	TT	E11-106R-003551
16.9 - 30	HD	R1	137 A6	8	W 15 L	W 14 L	429	1485	677	4455	700	TT	E11-106R-004470
16.9 - 30	SPECIAL	R1	143 A6	12	W 15 L	W 14 L	429	1485	687	4523	700	TL	
16.9 - 30	SPECIAL	R1	137 A6	8	W 15 L	W 14 L	429	1485	677	4455	700	TT	E11-106R-004470
16.9 - 30	SPECIAL	R1	143 A6	12	W 15 L	W 14 L	429	1485	687	4523	700	TT	E11-106R-003010
16.9 - 30 (14 - 30)	STANDARD	R1	146 A6	14	W 15 L	W 14 L	429	1485	677	4455	700	TT	E11-106R-005243
16.9 - 30	STANDARD	R1	137 A6	8	W 15 L	W 14 L	429	1485	677	4455	700	TT	E11-106R-003441
16.9 - 30	STANDARD	R1	139 A6	10	W 15 L	W 14 L	429	1485	677	4455	700	TT	E11-106R-004472
16.9 - 30	STANDARD	R1	143 A6	12	W 15 L	W 14 L	429	1485	687	4523	700	TT	
18.4 - 30	HD	R1	139 A6	8	W 16 L	W 15 L	467	1550	712	4719	725	TT	E11-106R-004435
18.4 - 30	HD	R1	149 A6	12	W 16 L	W 15 L	467	1550	712	4719	725	TT	E11-106R-004475
18.4 - 30	HD	R1	151 A6	14	W 16 L	W 15 L	467	1550	712	4719	725	TT	E11-106R-003615
18.4 - 30	SPECIAL	R1	149 A6	12	W 16 L	W 15 L	467	1550	712	4719	725	TT	E11-106R-004436
18.4 - 30	STANDARD	R1	139 A6	8	W 16 L	W 15 L	467	1550	712	4719	725	TT	E11-106R-004473

Printed on 4/25/2024 8:18 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..