

## TR 137 - Tekniska specifikationer



### Description

TR 137 är det BKT-däck som lämpar sig bäst för alla skördningsarbeten. Det är en garanti för utmärkt dragförmåga på åkern även med tung last. Däcket finns i flera versioner: Versionen med "stål förstärkt bälte" är extra slitstarkt mot punkteringar och skyddar mot alla former av skador inom användningsområdet. "HD"-versionen erbjuder extraordinär motståndskraft mot skärande underlag och punkteringar, liksom längre livslängd.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Lantbruk: Skördemaskin

Version	STANDARD
Type	TL
Tyre Size	24.5 - 32
LI/SS	156 A8

## Dimensions US Standard

Usa code	94004317
Ply Rating	12
Section Width (inch)	24.5
Overall Diameter (inch)	71.1
Static Loaded Radius (inch)	31.8
Rolling Circumference (inch)	210.4
Rim Rec	DW 21 B
Rim Alt	DW 20 B
ECE	E4-106R-002271
TRA Code	R1

## Load capacity (lbs)

mph / psi	24
25	8800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 2:21 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..