

TR 137 - Tekniska specifikationer



Description

TR 137 är det BKT-däck som lämpar sig bäst för alla skördningsarbeten. Det är en garanti för utmärkt dragförmåga på åkern även med tung last. Däcket finns i flera versioner: Versionen med "stålförstärkt bälte" är extra slitstarkt mot punkteringar och skyddar mot alla former av skador inom användningsområdet. "HD"-versionen erbjuder extraordinär motståndskraft mot skärande underlag och punkteringar, liksom längre livslängd.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Skördemaskin

Version	STANDARD
Type	TL
Tyre Size	24.5 - 32
LI/SS	159 A8

Dimensions US Standard

Usa code	94004324
Ply Rating	14
Section Width (inch)	24.5
Overall Diameter (inch)	71.1
Static Loaded Radius (inch)	31.8
Rolling Circumference (inch)	210.4
Rim Rec	DW 21 B
Rim Alt	DW 20 B
ECE	E4-106R-002273
TRA Code	R1

Load capacity (lbs)

mph / psi	28
25	9650

Printed on 4/26/2024 4:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..