

## TR 138 - Tekniska specifikationer



### Description

TR 138 är specialdesignat för teleskoplastare och grävlastare inom lantbruket. Det lämpar sig bäst för jordbearbetnings- och besprutningsarbeten. Utmärkt dragförmåga på mjuk jord, optimalt självrensande egenskaper och stabilitet är avgörande egenskaper som gör TR 138-däcket till det idealiska valet även vid de mest krävande markförhållanden.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Grävlastare • Teleskoplastare

Version	STANDARD
Type	TL
Tyre Size	17.5L - 24
LI/SS	151 A8

## Dimensions US Standard

Usa code	94061877
Ply Rating	12
Section Width (inch)	17.7
Overall Diameter (inch)	50.8
Static Loaded Radius (inch)	22.7
Rolling Circumference (inch)	151
Rim Rec	DW 15L
Rim Alt	DW 14L
ECE	E11-106R-005232

## Load capacity (lbs)

mph / psi	25
39	7605

Printed on 4/20/2024 10:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..