

## TR 144 - Tekniska specifikationer



### Description

TR 144 lämpar sig för att utrusta små traktorer som används till jordbearbetning. TR 144 ger enastående prestanda under alla driftförhållanden som kräver utomordentlig dragförmåga vid tung last. Det finns även i en "special"-version som passar särskilt väl till tung tjänst.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Liten traktor

|           |          |
|-----------|----------|
| Version   | STANDARD |
| Type      | TT       |
| Tyre Size | 7 - 16   |
| LI/SS     | 80 A8    |

## Dimensions US Standard

|                              |                     |
|------------------------------|---------------------|
| Usa code                     | 94052202            |
| Ply Rating                   | 6                   |
| Section Width (inch)         | 7.2                 |
| Overall Diameter (inch)      | 29.1                |
| Static Loaded Radius (inch)  | 13.7                |
| Rolling Circumference (inch) | 88.7                |
| Rim Rec                      | 6 L ; 6 LB ; 6.00 F |
| ECE                          | E11-106R-004322     |
| TRA Code                     | R1                  |

## Load capacity (lbs)

|  |           |     |
|--|-----------|-----|
|  | mph / psi | 36  |
|  | 25        | 990 |

Printed on 4/23/2024 1:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..