

## TR 145 - Ladda ned faktablad



### Description

TR 145 är särskilt konstruerat för små traktorer. Det specialutformade mönstret ger utmärkt dragförmåga och oöverträffade självrensande egenskaper. Den breda och djupa däckklacksdesignen säkerställer dessutom en längre däcklivslängd. TR 145-däcket har en stor kontaktyta för hög körkomfort och riktningstabilitet. &nbsp;

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Liten traktor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
160/90 - 12	STANDARD	R1	76 A6	6	4.00		160	631	294	1969	TT	E11-106R-005854

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/12/2024 11:39 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..