

TR 171 - Tekniska specifikationer



Description

TR 171 är ett däck med djupt mönster och lämpar sig för små traktorer som används till jordbearbetning. Tack vare däckets enastående självrensande egenskaper fungerar det utmärkt i våt och fuktig jord. TR 171 är designat med en speciell gummiblandning som ger utmärkt dragförmåga och extraordinär hållbarhet, även under de mest krävande arbetsförhållanden.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TT
Tyre Size	12.4 - 26
LI/SS	117 A8

Dimensions US Standard

Usa code	94034826
Ply Rating	8
Section Width (inch)	12.4
Overall Diameter (inch)	47.6
Static Loaded Radius (inch)	22.6
Rolling Circumference (inch)	146.7
Rim Rec	W 11
Rim Alt	W 10 ; W 9
ECE	E11-106R-003666
TRA Code	R1W+

Load capacity (lbs)

mph / psi	34
25	2830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 6:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..