

TR 317 - Tekniska specifikationer



Description

TR 317 är ett däck som lämpar sig för användning inom kommun och jordbearbetning med arbetsfordon, dikningsmaskiner och skördemaskiner för fruktodling. TR 317-däcket har en stor kontaktyta som ger utmärkt grepp och enastående stabilitet under alla förhållanden samt besitter fantastiska självrensande egenskaper.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon • Skördemaskin för fruktodling •
Dikningsmaskin

Version	HD
Type	TL
Tyre Size	18 X 8.50 - 8

Dimensions International Standard

Ply Rating	6
Section Width (mm)	215
Overall Diameter (mm)	450
Static Loaded Radius (mm)	198
Rolling Circumference (mm)	1305
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90

Load capacity (Kg)

km/h / bar	2.30
15	475

Printed on 4/24/2024 12:20 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..