

## TR 387 IND - Tekniska specifikationer



### Description

TR 387 IND är ett industridäck lämpligt för industriella släpvagnar och komprimatorer. Det har hög belastningskapacitet och finns i olika versioner för att möta specifika användarkrav när det gäller skär- och flismotstånd, tung användning och hållbarhet. Versionen med två kulor är särskilt lämplig för industritraktorer och transporter med släpvagnar.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industri: Kompaktfordon • Traktor • Släpvagn

Version	DUAL BEAD HD
Type	TL
Tyre Size	620/75 - 30 (23.1 - 30)
LI/SS	160 A8

## Dimensions US Standard

Usa code	94065325
Ply Rating	18
Section Width (inch)	23.8
Overall Diameter (inch)	65.9
Rim Rec	DW 20 A ; DW 20 B
TRA Code	R3

## Load capacity (lbs)

mph / psi	38
25	11000

Printed on 4/20/2024 5:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..