

## TR 387 - Tekniska specifikationer



### Description

TR 387 är ett industridäck för lantbruket som lämpar sig för sockerrörssläp och packningsfordon. Det har enastående hög lastkapacitet i kombination med en längre livslängd och finns i olika versioner för att uppfylla olika användarbehov vad gäller motståndskraft mot skärande underlag och punkteringar, tung användning och hållbarhet. Versionen med dubbel vulst lämpar sig särskilt väl för industritraktorer och transporter med släp.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Släpvagn

Industri: Kompaktfordon

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TL        |
| Tyre Size | 12.4 - 28 |
| LI/SS     | 120 A8    |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94004959        |
| Ply Rating                   | 8               |
| Section Width (inch)         | 12.8            |
| Overall Diameter (inch)      | 47.2            |
| Static Loaded Radius (inch)  | 21.7            |
| Rolling Circumference (inch) | 140.8           |
| Rim Rec                      | W 11            |
| Rim Alt                      | W 9 ; W 10      |
| ECE                          | E11-106R-005277 |
| TRA Code                     | R3              |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 34   |
| 25        | 3090 |

Printed on 4/26/2024 11:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..