TR 387 - Tekniska specifikationer

Description

TR 387 är ett industridäck för lantbruket som lämpar sig för sockerrörssläp och packningsfordon. Det har enastående hög lastkapacitet i kombination med en längre livslängd och finns i olika versioner för att uppfylla olika användarbehov vad gäller motståndskraft mot skärande underlag och punkteringar, tung användning och hållbarhet. Versionen med dubbel vulst lämpar sig särskilt väl för industritraktorer och transporter med släp.

UM

US Standard

Construction

BIAS

Machinery

Lantbruk: Släpvagn
Industri: Kompaktfordon

Version	DUAL BEAD HD
Type	TT
Tyre Size	23.1 - 26
LI/SS	157 A8

Dimensions US Standard

Usa code	94027767
Ply Rating	18
Section Width (inch)	23.3
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	184.6
Rim Rec	DW 20 B
TRA Code	R3

Load capacity (lbs)

mph / psi	38
25	9090

Printed on 4/18/2024 6:09 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..