

TR 390 IND - Ladda ned faktablad



Description

TR 390 IND är ett industridäck lämpligt för industriella släpvagnar och komprimatorer. Det har hög belastningskapacitet och finns i olika versioner för att möta specifika användarkrav när det gäller skär- och flismotstånd, tung användning och hållbarhet. Versionen med två kulor är särskilt lämplig för industritraktorer och transporter med släpvagnar.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Kompaktfordon • Traktor • Släpvagn

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
28L - 26	DUAL BEAD HD	R3	172 A6	20	DW 25 B	DW 23 B	714	1560	690	4545	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/12/2024 11:56 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..