

## TR 390 - Tekniska specifikationer



### Description

TR 390 är ett industridäck för lantbruket som lämpar sig för sockerrörssläp och packningsfordon. TR 390 har enastående lastkapacitet och lång hållbarhet. HD-versionen med dubbel vulst är särskilt lämpad för industritraktorer och transportarbeten med släp, och HD-versionen med dubbel vulst special är idealisk för tung tjänst.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Släpvagn

Industri: Kompaktfordon

|           |          |
|-----------|----------|
| Version   | STANDARD |
| Type      | TL       |
| Tyre Size | 28L - 26 |
| LI/SS     | 150 A8   |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94005239        |
| Ply Rating                   | 12              |
| Section Width (inch)         | 28.1            |
| Overall Diameter (inch)      | 61.4            |
| Static Loaded Radius (inch)  | 27.2            |
| Rolling Circumference (inch) | 178.9           |
| Rim Rec                      | DW 25 B         |
| Rim Alt                      | DW 23 B         |
| ECE                          | E11-106R-004608 |
| TRA Code                     | R3              |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 20   |
| 25        | 7400 |

Printed on 4/20/2024 1:15 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..