

TR 390 - Tekniska specifikationer



Description

TR 390 är ett industridäck för lantbruket som lämpar sig för sockerrörssläp och packningsfordon. TR 390 har enastående lastkapacitet och lång hållbarhet. HD-versionen med dubbel vulst är särskilt lämpad för industritraktorer och transportarbeten med släp, och HD-versionen med dubbel vulst special är idealisk för tung tjänst.

UM

US Standard

Construction

❖ BIAS

Machinery

Lantbruk: Släpvagn

Industri: Kompaktfordon

Version	DUAL BEAD HD
Type	TL
Tyre Size	28L - 26
LI/SS	168 A8

Dimensions US Standard

Usa code	94047048
Ply Rating	20
Section Width (inch)	28.1
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	178.9
Rim Rec	DW 25 B
Rim Alt	DW 23 B
ECE	E11-106R-004609
TRA Code	R3

Load capacity (lbs)

mph / psi	42
25	12350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 10:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..