

## TR 393 - Tekniska specifikationer



### Description

TR 393 är specialkonstruerat för balpressar, spridare och arbetsfordon för körning på både väg och åker. Den speciella mönsterdesignen ger optimal flotation och självrensande egenskaper, samt lång livslängd. Tack vare den stora kontaktytan ger TR 393 utmärkt dragförmåga och minimerar jordpackning.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Balpress • Arbetsfordon • Spridare

Version	STANDARD
Type	TL
Tyre Size	21.5L - 16.1 SL
LI/SS	146 B

## Dimensions US Standard

Usa code	94075171
Ply Rating	10
Section Width (inch)	21.5
Overall Diameter (inch)	45.4
Rim Rec	W 18 CH
Rim Alt	W 16 CH
TRA Code	I2

## Load capacity (lbs)

mph / psi	28
30	6600

Printed on 4/24/2024 4:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..