

TR 459 - Tekniska specifikationer



Description

TR 459 har designats särskilt för gräv- och lastarbeten samt användning inom kommun och underhåll med traktor och grävlastare. Det ger hög stabilitet och är tillgängligt i två versioner. "Special"-versionen har längre livslängd.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Grävlastare • Traktor
Industri: Grävlastare

Version	INDUSTRIAL
Type	TL
Tyre Size	19.5L - 24
LI/SS	147 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	490
Overall Diameter (mm)	1333
Static Loaded Radius (mm)	585
Rolling Circumference (mm)	4031
Rim Rec	DW 16 L
ECE	E11-106R-005334
TRA Code	R4

Load capacity (Kg)

km/h / bar	1.90
40	3075

Printed on 5/6/2024 8:51 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..