

TR 461 - Tekniska specifikationer



Description

TR 461 har ett BKT-mönster som passar traktorer för kommunala arbeten och underhållsarbeten samt lastningsarbeten med teleskoplastare. Skyddet för sidoväggen ger det här däck utmärkt stabilitet och ett utomordentligt skydd mot skär- och skrapskador, vilket ger längre livslängd även på hårda ytor.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Grävlastare • Teleskoplastare • Traktor

Version	STANDARD
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	138 A8
LI/SS FREE ROLLING	150 A8

Dimensions International Standard

Ply Rating	18
Section Width (mm)	305
Overall Diameter (mm)	987
Static Loaded Radius (mm)	435
Rolling Circumference (mm)	2902
Rim Rec	W 9
Rim Alt	11
ECE	E11-106R-006914
TRA Code	R4

Load capacity (Kg)

	km/h / bar	5.50
	10 FR	4690
	25 FR	3985
	30 FR	3750
	40 FR	3350
	10 DW	3305
	25 DW	2810
	30 DW	2645
	40 DW	2360

Printed on 4/24/2024 8:27 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..