TR 461 - Tekniska specifikationer

Description

TR 461 har ett BKT-mönster som passar traktorer för kommunala arbeten och underhållsarbeten samt lastningsarbeten med teleskoplastare. Skyddet för sidoväggen ger det här däcket utmärkt stabilitet och ett utomordentligt skydd mot skär- och skrapskador, vilket ger längre livslängd även på hårda ytor.

UM

International Standard

Construction

BIAS

Machinery

Industri: Grävlastare • Teleskoplastare • Traktor

Version	STANDARD
Type	TL
Tyre Size	16.9 - 28
LI/SS	154 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	440
Overall Diameter (mm)	1390
Static Loaded Radius (mm)	620
Rolling Circumference (mm)	4087
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

Load capacity (Kg)

km/h / bar	2.90
40	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 8:11 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..