TR 461 - Tekniska specifikationer

Description

TR 461 har ett BKT-mönster som passar traktorer för kommunala arbeten och underhållsarbeten samt lastningsarbeten med teleskoplastare. Skyddet för sidoväggen ger det här däcket utmärkt stabilitet och ett utomordentligt skydd mot skär- och skrapskador, vilket ger längre livslängd även på hårda ytor.

UM

International Standard

Construction

BIAS

Machinery

Industri: Grävlastare • Teleskoplastare • Traktor

Version	STANDARD
Type	TL
Tyre Size	19.5L - 24
LI/SS	151 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	490
Overall Diameter (mm)	1310
Static Loaded Radius (mm)	578
Rolling Circumference (mm)	3851
Rim Rec	DW 16 L
TRA Code	R4

Load capacity (Kg)

km/h / bar	2.30
40	3450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 10:32 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..