TR 461 - Ladda ned faktablad

Description

TR 461 har ett BKT-mönster som passar traktorer för kommunala arbeten och underhållsarbeten samt lastningsarbeten med teleskoplastare. Skyddet för sidoväggen ger det här däcket utmärkt stabilitet och ett utomordentligt skydd mot skär- och skrapskador, vilket ger längre livslängd även på hårda ytor.

UM

US Standard

Construction

BIAS

Machinery

Industri: Grävlastare • Teleskoplastare • Traktor

SIZE	Version	USACode	TRA Code	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
12.5/80 - 18	STANDARD	94067428	R4		138 A8	150 A8	18	W 9	11	12	38.9	17.1	114.3	TL	E11-106R-006914
12.5/80 - 18	STANDARD	94028344	R4		129 A8	142 A8	12	W 9	11	12	38.9	17.1	114.3	TL	E11-106R-005367
16.9 - 24	STANDARD	94016747	R4	151 A8			14	DW 15 L	DW 14 L	17.3	50.4	22.3	148.1	TL	
19.5L - 24	STANDARD	94016761	R4	151 A8			12	DW 16 L		19.3	51.6	22.8	151.6	TL	
19.5L - 24	STANDARD	94016778	R4	154 A8			14	DW 16 L		19.3	51.6	22.8	151.6	TL	
21L - 24	STANDARD	94016785	R4	157 A8			14	DW 18 L		21.3	54.5	23.9	160.3	TL	
16.9 - 28	STANDARD	94016754	R4	154 A8			14	DW 15 L	DW 14 L	17.3	54.7	24.4	160.9	TL	
620/60 B 34	HD	94067015	R4	175 A8				DW 20 B		24.2	64.1	29.5	194.1	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 10:45 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..