



## TR 675 - Ladda ned faktablad



### Description

TR 675 är ett diagonaldäck särskilt konstruerat för skogsbruk. Den robusta däckklacksdesignen ger utmärkt dragförmåga och självrensande egenskaper, samtidigt som däckhöljets starka struktur ger hög lastkapacitet och stålbälten skyddar däcket från punkteringar och skador. Gummiblandningen i TR 675 ger hög motståndskraft mot skärande underlag och punkteringar även i svår terräng och under extrema förhållanden.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Skotare

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
540/65 - 28	STEEL BELTED	94059959	LS2	155 A8/161 A2	16	W 16 L	W 18 L	20.9	56.1	26.1	174.8	TL	E11-106R-005271

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/7/2024 1:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..