



TR 678 IND - Tekniska specifikationer

□

Description

TR 678 IND är speciellt konstruerad för industriella åtgärder. Dess robusta kantutformning ger utmärkt dragkraft och är självrengörande. Den starka höljkonstruktionen står för hög lastkapacitet medan stålremmen skyddar däcket mot punkteringar och skador. TR 678 har en skärbeständig spår bana som ger utmärkt skär-och-flisresistans även på svår terräng under extrema förhållanden.

UM

US Standard

Construction

BIAS

Machinery

Industri: Grävmaskin, Släpvagn

Version	DUAL BEAD
Type	TL
Tyre Size	600/40 - 22.5
LI/SS DRIVE WHEEL	157 A8
LI/SS FREE ROLLING	169 A8

Dimensions US Standard

Usa code	94065301
Section Width (inch)	24.2
Overall Diameter (inch)	42.7
Static Loaded Radius (inch)	19
Rolling Circumference (inch)	128.5
Rim Rec	AG 20.00
ECE	E11-106R-006973

Load capacity (lbs)

mph / psi	
25 FR	12790
25 DW	9090

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..