


## TR 678 IND - Ladda ned faktablad



### Description

TR 678 IND är speciellt konstruerad för industriella åtgärder. Dess robusta kantutformning ger utmärkt dragkraft och är självrengörande. Den starka höljkonstruktionen står för hög lastkapacitet medan stålremmen skyddar däcket mot punkteringar och skador. TR 678 har en skärbeständig spårband som ger utmärkt skär-och-flisresistans även på svår terräng under extrema förhållanden.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industri: Grävmaskin • Släpvagn

| SIZE          | Version   | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | RIM REC  | RIM ALT | SW  | OD   | SLR | RC   | Type | ECE             |
|---------------|-----------|-------------------|--------------------|----------|---------|-----|------|-----|------|------|-----------------|
| 600/40 - 22.5 | DUAL BEAD | 157 A8            | 169 A8             | AG 20.00 |         | 615 | 1085 | 483 | 3264 | TL   | E11-106R-006973 |

Printed on 4/25/2024 5:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..