


TR 678 IND - Ladda ned faktablad



Description

TR 678 IND är speciellt konstruerad för industriella åtgärder. Dess robusta kantutformning ger utmärkt dragkraft och är självrengörande. Den starka höljkonstruktionen står för hög lastkapacitet medan stålremmen skyddar däckets mot punkteringar och skador. TR 678 har en skärbeständig spårband som ger utmärkt skär-och-flisresistans även på svår terräng under extrema förhållanden.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Grävmaskin • Släpvagn

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
600/40 - 22.5	DUAL BEAD	94065301	157 A8	169 A8	AG 20.00		24.2	42.7	19	128.5	TL	E11-106R- 006973

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/22/2025 5:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..