

TR 678 - Tekniska specifikationer



Description

TR 678 är särskilt konstruerat för skogsbruk. Den robusta däckklacksdesignen ger utmärkt dragförmåga och självrensande egenskaper. Däckhöljets starka struktur ger hög lastkapacitet, och stålbalten skyddar däckets från punkteringar och skador. TR 678 är tillverkat av en skärbeständig gummiblandning som ger utmärkt motståndskraft mot skärande underlag och punkteringar även i svår terräng och under extrema förhållanden.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon • Släpvagn
Industri: Grävmaskin • Släpvagn

| | |
|-----------|---------------|
| Version | STEEL BELTED |
| Type | TL |
| Tyre Size | 600/65 - 34 |
| LI/SS | 164 A2/160 A6 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94032679 |
| Ply Rating | 14 |
| Section Width (inch) | 24 |
| Overall Diameter (inch) | 64.7 |
| Static Loaded Radius (inch) | 29.8 |
| Rolling Circumference (inch) | 193.5 |
| Rim Rec | DW 20 B |
| ECE | E11-106R-003648 |
| TRA Code | LS2 |

Load capacity (lbs)

| mph / psi | 35 |
|-----------|-------|
| 20 | 9920 |
| 5 | 11020 |

Printed on 4/26/2024 8:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..