

## TR 882 - Tekniska specifikationer



### Description

TR 882 är ett väldigt mångsidigt däck som lämpar sig för flera tillämpningar och fordon. Det har konstruerats för att passa till arbetsfordon, skördemaskiner/balpressar och sockerrörsmaskiner. Den speciella gummiblandningen minimerar risken för skador och däcket har dessutom utmärkt hållbarhet och dragförmåga under alla arbetsförhållanden på åkern. TR 882 finns även i versioner som "med stålförstärkt bälte", "HD" och "special" för att uppfylla specifika kundbehov.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Lantbruk: Balpress • Höskördemaskin • Arbetsfordon •  
Släpvagn  
Industri: Släpvagn

|                    |               |
|--------------------|---------------|
| Version            | ARAMID BELTED |
| Type               | TL            |
| Tyre Size          | 400/60 - 15.5 |
| LI/SS DRIVE WHEEL  | 132 A8        |
| LI/SS FREE ROLLING | 145 A8        |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Ply Rating                 | 14              |
| Section Width (mm)         | 400             |
| Overall Diameter (mm)      | 875             |
| Static Loaded Radius (mm)  | 378             |
| Rolling Circumference (mm) | 2605            |
| SRI (mm)                   | 410             |
| Rim Rec                    | AG 13.00        |
| ECE                        | E11-106R-004331 |

## Load capacity (Kg)

| km/h / bar | 3.60 |
|------------|------|
| 10 FR      | 4060 |
| 25 FR      | 3450 |
| 30 FR      | 3250 |
| 40 FR      | 2900 |
| 10 DW      | 2800 |
| 25 DW      | 2380 |
| 30 DW      | 2240 |
| 40 DW      | 2000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 2/13/2025 5:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..