

TRAC FARM PLUS - Tekniska specifikationer



Description

TRAC FARM PLUS är ett bakdäck för traktorer konstruerat särskilt för användning vid jordbearbetnings- och transportarbeten. Däcket har ett djupare mönster med dubbla, vinklade däckklackar som ger både utmärkt dragförmåga och bekväm körning på väg. Det speciella däcktjänstret med större kontaktyta ger högre stabilitet och själrensande egenskaper. TRAC FARM PLUS är en garanti för längre livslängd.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TT
Tyre Size	16.9 - 28
LI/SS	143 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	440
Overall Diameter (mm)	1435
Static Loaded Radius (mm)	660
Rolling Circumference (mm)	4298
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-003627
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.40
30	2725

Printed on 2/3/2023 4:52 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..