

## TRAC FARM PLUS - Tekniska specifikationer



### Description

TRAC FARM PLUS är ett bakdäck för traktorer konstruerat särskilt för användning vid jordbearbetnings- och transportarbeten. Däcket har ett djupare mönster med dubbla, vinklade däckklackar som ger både utmärkt dragförmåga och bekväm körning på väg. Det speciella däkmönstret med större kontaktyta ger högre stabilitet och själrensande egenskaper. TRAC FARM PLUS är en garanti för längre livslängd.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TT
Tyre Size	16.9 - 30
LI/SS	144 A6

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	440
Overall Diameter (mm)	1475
Static Loaded Radius (mm)	679
Rolling Circumference (mm)	4466
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-004529
TRA Code	R1

## Load capacity (Kg)

km/h / bar	2.40
30	2800

Printed on 2/3/2023 4:09 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..