TRAC FARM - Tekniska specifikationer

Description

TRAC FARM är ett robust däck konstruerat särskilt för traktorer som används till jordbearbetnings- och transportarbeten. Det djupa mönstret och en speciell gummiblandning som ger motståndskraft mot skärande underlag och punkteringar gör däcket lämpligt för de mest krävande driftförhållanden och är en garanti för maximal valuta för pengarna under hela livslängden. TRAC FARM är designat med fler däckklackar för enastående dragförmåga och självrensande egenskaper.

UM

US Standard

Construction

BIAS

Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TT
Tyre Size	18.4 - 30
LI/SS	147 A8

Dimensions US Standard

Usa code	94043743
Ply Rating	14
Section Width (inch)	18.5
Overall Diameter (inch)	61.6
Static Loaded Radius (inch)	28.2
Rolling Circumference (inch)	179.4
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-004525
TRA Code	R1

Load capacity (lbs)

mph / psi	38
25	6780

Printed on 4/26/2024 3:14 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..