

TRAC GRADER + - Tekniska specifikationer



Description

TRAC GRADER + (G-2) är ett diagonaldäck för väghyvlar. Det är ett utmärkt val för budgetmedvetna kunder. Det pålitliga höljet är byggt för att hålla. Den självrensande mönsterdesignen har ett öppet block-/mönsterförhållande som ger bästa möjliga dragkraft under alla förhållanden. Specialversionen är tillverkad av en speciell skär- och rivtålig gummiblandning.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Väghyvlare

Version	STANDARD
Type	TT
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	12
Overall Width (mm)	364
Overall Diameter (mm)	1348
Static Loaded Radius (mm)	598
Rolling Circumference (mm)	3990
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00 VA SDC; 10.00 WA SDC
TRA Code	G2

Load capacity (Kg)

km/h / bar	2.50
40	3075

Printed on 4/28/2024 2:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..