

TRAC MASTER - Tekniska specifikationer



Description

TRAC MASTER är ett däck för jordbearbetning, gräsmatta och trädgård och lämpar sig för små traktorer och arbetsfordon. Mönsterdesignen bevarar marken på bästa vis och ger samtidigt utmärkt dragförmåga på åkern och optimala själrensande egenskaper.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon • Liten traktor

Version	STANDARD
Type	TL
Tyre Size	300/60 - 12

Dimensions International Standard

Ply Rating	8
Section Width (mm)	306
Overall Diameter (mm)	645
Static Loaded Radius (mm)	285
Rolling Circumference (mm)	1885
Rim Rec	10.5
Rim Alt	9.5
ECE	E11-106R-003597

Load capacity (Kg)

km/h / bar	3.20
50	1030

Printed on 5/7/2024 1:24 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..