

TRAC MASTER - Tekniska specifikationer



Description

TRAC MASTER är ett däck för jordbearbetning, gräsmatta och trädgård och lämpar sig för små traktorer och arbetsfordon. Mönsterdesignen bevarar marken på bästa vis och ger samtidigt utmärkt dragförmåga på åkern och optimala själrensande egenskaper.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon • Liten traktor

Version	STANDARD
Type	TL
Tyre Size	33 X 15.50 - 15

Dimensions International Standard

Ply Rating	8
Section Width (mm)	404
Overall Diameter (mm)	865
Static Loaded Radius (mm)	378
Rolling Circumference (mm)	2526
Rim Rec	13 LB
ECE	E4-106R-002330

Load capacity (Kg)

km/h / bar	3.10
50	1620

Printed on 5/7/2024 2:10 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..