

TRAC SUPER - Tekniska specifikationer



Description

TRAC SUPER är det första radialdäcket som lanseras i BKT:s kommunsortiment. Däckstrukturen med stålbalte garanterar mjuk körning kombinerad med optimal dragförmåga. Det innebär att däcket lämpar sig särskilt väl för användning på stora gräsytor som parker och vägrenar.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Liten traktor

| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 400/50 R 15 |
| LI/SS | 118 A8/B |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 380 |
| Overall Diameter (mm) | 775 |
| Static Loaded Radius (mm) | 329 |
| Rolling Circumference (mm) | 2269 |
| SRI (mm) | 370 |
| Rim Rec | 13.00 |
| ECE | E11-106R-009073 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 |
|------------|------|------|------|
| 50 | 845 | 1085 | 1320 |
| 40 | 845 | 1085 | 1320 |
| 30 | 950 | 1215 | 1480 |
| 20 | 1070 | 1370 | 1665 |
| 10 | 1185 | 1520 | 1850 |

Printed on 4/24/2024 6:26 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..