

## TRAC SUPER - Tekniska specifikationer



### Description

TRAC SUPER är det första radialdäcket som lanseras i BKT:s kommunsortiment. Däckstrukturen med stålbalte garanterar mjuk körning kombinerad med optimal dragförmåga. Det innebär att däcket lämpar sig särskilt väl för användning på stora gräsytor som parker och vägrenar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Liten traktor

Version	STANDARD
Type	TL
Tyre Size	400/50 R 15
LI/SS	118 A8/B

## Dimensions US Standard

Usa code	94075300
Section Width (inch)	15
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	13
Rolling Circumference (inch)	89.3
Rim Rec	13.00
ECE	E11-106R-009073

## Load capacity (lbs)

mph / psi	12	17	23
30	1870	2400	2910
25	1870	2400	2910
20	2100	2680	3270
10	2360	3030	3680
5	2620	3360	4080

Printed on 4/24/2024 10:51 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..