

V-FLEXA - Tekniska specifikationer



Description

V-FLEXA är ett radialdäck som har tagits fram speciellt för släpvagnar inom lantbruket. Det här är en senaste generationens flotationsprodukt med VF-teknologi, som kan användas till tunga lasttransporter både på åker och väg med ett ringtryck som är 30 procent lägre än hos ett standarddäck i samma storlek. Extra stålbälten ger däckhöljet maximal motståndskraft mot stötar. Inte nog med att V-FLEXA klarar tunga laster med bibehållen säkerhet – det undviker också jordpackning tack vare den perfekta viktfordelningen. Dessutom erbjuder V-FLEXA fantastiska självrensande egenskaper, hållbarhet samt lågt rullningsmotstånd.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Släpvagn

| | |
|--------------------|------------------|
| Version | STEEL BELTED |
| Type | TL |
| Tyre Size | VF 750/45 R 26.5 |
| LI/SS | 176 D |
| LI/SS DRIVE WHEEL | 176 D |
| LI/SS FREE ROLLING | 176 D |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94074822 |
| Section Width (inch) | 29.7 |
| Overall Diameter (inch) | 53.1 |
| Static Loaded Radius (inch) | 23 |
| Rolling Circumference (inch) | 161.2 |
| Rim Rec | AG 24.00 |
| ECE | E11-106R-008832 |

Load capacity (lbs)

| mph / psi | 12 | 17 | 23 | 29 | 35 | 41 | 46 |
|-----------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 5710 | 7280 | 8560 | 9990 | 11270 | 12840 | 14260 |
| 40 | 6270 | 8000 | 9400 | 10960 | 12370 | 14090 | 15660 |
| 30 | 7330 | 9350 | 11010 | 12840 | 14480 | 16490 | 18320 |
| 25 | 8080 | 10310 | 12130 | 14150 | 15970 | 18180 | 20200 |
| 5 | 10280 | 13100 | 15410 | 17980 | 20290 | 23120 | 25680 |

Printed on 4/27/2024 5:00 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..