

XL GRIP (ADT) - Tekniska specifikationer



Description

XL GRIP (ADT) är ett däck med vinkelskikt för ramstyrda dumpers konstruerat för att minimera revor och punkteringar under tuffa förhållanden där exceptionell dragförmåga krävs. Funktionerna bidrar till längre livslängd för däck.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Ramstyrd dumper (ADT)

Version	STANDARD
Type	TL
Tyre Size	26.5 - 25

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	680
Overall Diameter (mm)	1740
Static Loaded Radius (mm)	796
Rolling Circumference (mm)	5150
Rim Rec	22.00/3.0
TRA Code	E3

Load capacity (Kg)

km/h / bar	4.25
50	11200

Printed on 4/17/2024 5:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..